

Shieldfiber UHPC13

Steel Fibers



MICSHIELD®

Description

Shieldfiber UHPC13 is a Steel Fiber designed for Ultra High-Performance Concrete (UHPC).

Geometry

Length (l)	13 mm
Diameter (d)	0.20 mm
Aspect Ratio	65 (l/d)

Typical Properties

Base Material	Bright, High Carbon wire
Nominal tensile strength	2.750 (N/mm ²)
Young's modulus	200.000 (N/mm ²)
Fiber Volume Content	311.518 fibers/kg
Fiber Network	242.984 m/m ³ at 60 kg/m ³

Dosage

Dosages of 1.5–3 vol.% steel fibers allow UHPC to develop a strain-hardening response.

Packaging

Shieldfiber UHPC13 is supplied in 20 kg bags. .

Shelf Life and Storage

Shieldfiber UHPC13 has a shelf life of 12 months when stored in its original unopened packaging in dry conditions.

Shelf life may be reduced if the recommended storage conditions changed.

Address: Manaseer Group, 8th Circle, King Abdullah II St. 302
P.O. Box 925988 Amman, 11110, Jordan

Phone +962 6 5800600
Fax. +962 6 5833890

Email: info.shield@manaseer-ic.com
Website: www.manaseergroup.com

LEGAL DISCLAIMER: All information provided, and recommendations made herein are intended to assist customers in determining whether our products are suitable for their applications. We request that customers inspect and test our products before use in order to make their own final decision regarding suitability. We do not guarantee results, freedom from patent infringement, or suitability of resultant products for any suggested application with respect to the use of any formula or material described herein

Version 250915 SP-FB –UHPC13-001