# Shieldfoam EPS

### **Expanded Polystyrene Sheets**



#### Description

**Shieldfoam EPS** is a plastic foam material made from solid polystyrene beads, forming a closed-cell rigid structure with styrene creating the cellular framework and pentane serving as the blowing agent.

#### Uses

- Provides thermal insulation in region of high temperatures (80°C or above).
- Used to create voids in concrete structures to reduce weight without losing strength.
- Used as backfill behind retaining walls to reduce soil pressure.
- Applied in internal and external wall insulation systems (ETICS).
- Helps reduce noise transmission in walls and floors.
- Commonly used in packaging and storage applications

#### **Characteristics / Advantages**

- Available in wide range of thicknesses.
- Excellent thermal insulation with low thermal conductivity.
- Long-term thermal insulation performance.
- Extremely lightweight and cushioning.
- Low moisture absorption.
- Chemical resistance.

#### **Standard Compliance**

ASTM C578, Type II.

## **Technical Support**

Refer to contacting technical information, method statement or technical support team for any inquiry.

#### **Typical Properties**

Color	White
Density (ASTM C578, C303)	20 kg/cm <sup>3</sup>
R-Value (ASTM C578, ASTM C518) Per 1-inch thickness @ 23.9°C .	4
Compressive Strength @1% Deformation (Max) (ASTM C578 - D1621)	31 kPa
Compressive Strength @5% Deformation (Max) (ASTM C578 - D1621)	68 kPa
Compressive Strength @ 10% Deformation (Min) (ASTM C578 - D1621)	103 kPa
Flexural Strength (Min) (ASTM C578 - C203)	240 KPa
Water Absorption (% by volume)(ASTM C578 - C272)	3
Vapor Permeability max. at 23°C (AS 2498.5)	580 μg/m².s
Coefficient of Thermal Expansion (ASTM C578 – D696)	6.3 x 10 <sup>-5</sup> m/m°K
Flame Propagation – Eight Value (min.) (AS 2122.1)	19%

#### **Shelf Life and Storage**

**Shieldfoam EPS** has an unlimited shelf life when stored in cool and dry conditions, protected from direct sunlight, heat, and moisture.

Address: Manaseer Group, 8th Circle, King Abdullah II St. 302 P.O. Box 925988 Amman, 11110, Jordan

Phone +962 6 5800600 Fax. +962 6 5833890 Email: info.shield@manaseer-ic.com Website: www.manaseergroup.com

**LEGAL DISCLAIMER**: All information provided, and recommendations made herein are intended to assist customers in determining whether our products are suitable for their applications. We request that customers inspect and test our products before use in order to make their own final decision regarding suitability. We do not guarantee results, freedom from patent infringement, or suitability of resultant products for any suggested application with respect to the use of any formula or material described herein.

Version 251008 SP-FB - EPS-001

Manaseer Industrial Complex







