

Shieldprotect C

Non-staining, Water-based Silicate Water Repellent



Description

Shieldprotect C is a one-component, water-based, breathable, and non-absorbent water repellent, based on Silicate, designed to reduce the absorption of water and water-borne salts by impregnation inside substrates.

Uses

- To provide a water-repellent surface on all types of new and existing structures like building stone, bricks, masonry units, plasters, etc.
- Effective in coastal environments.

Characteristics / Advantages

- Single component and non-absorbent liquid.
- Ready to use, colorless liquid.
- Penetrates through substrate pores.
- Highly resistant to weathering conditions.
- Protects stone against the penetration of water.

Shelf Life and Storage

Shieldprotect C has a shelf life of 12 months when stored in its original unopened packaging in dry conditions. Shelf life may be reduced if the recommended storage conditions changed.

Consumption

Approximately 0.20 – 0.40 L per m²

Note: This coverage is theoretical and may vary due to site wastage, substrate roughness/ porosity, and absorption rate.

Typical Properties

Color	Clear
Appearance	Liquid
Specific Gravity (@ 23°C)	1.00 ± 0.02
Rapid Chloride Permeability (ASTM C1202)	Low
Full Cure	48 – 72 hours

Packaging

Shieldprotect C is supplied in 5, 20-litre pails.

Safety Instructions

Avoid contact with the eyes and skin. In case of direct contact with the skin, wash the affected area immediately with water for several minutes. If it comes into contact with the eyes, rinse immediately with lukewarm water for at least 15 minutes and get medical advice or treatment if any emergency warning signs appear.

For further information, refer to the Material Safety Data Sheet

Application Instructions

1. Surface Preparation

The substrate must be sound and clean from dust, oils, dirt, grease, curing compounds or any contaminants. Laitance shall be removed by mechanical means. Substrates should be also sufficiently cured to avoid any shrinkage cracks.

2. Application

To achieve the perfect penetration property, the correct rate and method of application are necessary.

Shieldprotect C can be applied by brush, roller, or low-pressure sprayer. Avoid exposure to water within a minimum of 3 – 4 hours after application.

Number of coats :	2 coats are recommended
Overcoating time :	Allow to dry for a minimum of 2 hours (at 20°C) before applying the next layer.

3. Cleaning

All mixing equipment and application tools should be cleaned immediately with clean water. Hardened material should be mechanically removed.

Technical Support

Refer to technical information, method statement, or contact technical support team for any inquiry.

Address: Manaseer Group, 8th Circle, King Abdullah II St. 302
P.O. Box 925988 Amman, 11110, Jordan

Phone +962 6 5800600
Fax. +962 6 5833890

Email: info.shield@manaseer-ic.com
Website: www.manaseergroup.com

LEGAL DISCLAIMER: All information provided, and recommendations made herein are intended to assist customers in determining whether our products are suitable for their applications. We request that customers inspect and test our products before use in order to make their own final decision regarding suitability. We do not guarantee results, freedom from patent infringement, or suitability of resultant products for any suggested application with respect to the use of any formula or material described herein.

Version 250727 SP-AF –Protect C-003